



Add: No.12, Jinling Road, Zhongkai Hi-tech Development Zone,
Huizhou City, Guangdong, China 516006
Tel: 86-752-2771789 Fax: 86-752-2771684
Email: marketing@hi-zealed.com
Web: www.hzleddriver.com

HZD024MTI-CV

24W Triac Dimmable LED Driver

Product Features

- Constant voltage output. can load 16-24W.
- Class 2 LED power supply, Double-isolated.
- Short circuit, over current and over voltage protection. Efficiency up to 83% .
- Compatible with both leading edge and trailing edge led dimmer ,5-100% logarithmic dimming range.
- Compatible with many kinds of dimming system, such as Siemens、Lutron、Schneider Clipsal Leviton etc.
- 3 years quality warranty

Technical Specifications

Model No.	Output Power	Input Voltage Range	AC-Frequency	Standby Power	Output Current	On Load Voltage	Power Factor	Efficiency	Dimensions	Weight
HZD024 MTI-CV	24 W	100-120V/ 200-240V AC	50-60Hz	0.25A Max	1600mA	12V	>0.95	84%	120*42*27 mmm	120g
					1000mA	24V				


Environmental Specifications

Operating Temperature	-30~45°C
Storage Temperature	-40~+70°C
Thermal Dissipation	Nature
Relative Humidity	5~95%
Isolation Voltage	In/Out 3000VAC
Vibration	5-55Hz/2g, 30 Minutes
Life Time	18000Hours, at TC max

Conformity & Standards

EMI	EN55022 EN55015 Class B
Safety	EN60598
Electromagnetic Immunity	EN61547, EN5024 EN61000-4-2/3/4/6/8/11
Harmonic Current Emissions	EN61000-3-2 EN61000-3-3

Installation Introduction



Dimensions Chart

